

**SPECIFICATION DATA SHEET | MODEL : 400TTS**



**TRANSTAINER 15809 GALLON CONTAINER STATIC:** Static fuel tank container, 110% containment, pump cabinet c/w equipment storage area, built to ULC and UL, BS799 Part 5 & complies with PPG2 Regulations.

- ❖ 110% double wall fuel storage container to comply with Environmental regulations.
- ❖ CSC plated - made to Convention for Safe Container Standard.
- ❖ Corner twist locks top and bottom for ease of handling.
- ❖ Can be stacked 6 high full of fuel, reducing storage space requirements and when on location.
- ❖ Pump, valves, outlets and fittings are all housed within the lockable cabinet which is fitted with a spill catchment sump.
- ❖ Auxiliary feed and return outlets are all top mounted to help prevent fuel leakage with 3" tank battery bottom Outlets.
- ❖ For additional security, hoses can be fed through any of the 4 letterboxes enabling doors to be kept locked whilst in use.
- ❖ Quality contents and bund gauges.
- ❖ 3" Fast fill fuel connection in cabinet with high performance overflow prevention device.
- ❖ Access ladder to operating platform for top filling and maintenance operations on both sides with kick plates
- ❖ Inner tank can be accessed via x2 manholes for maintenance and inspection.
- ❖ Option for up to 4 sets of feed & return connections plus pump/auxiliary equipment feed.
- ❖ Marine specification paint and application Ral 9001 White

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge; 3" fill point; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; UL Emergency vent; Extended normal vent pipe; lockable front cabinet area.	
<b>Capacity Litres:</b> 59847	<b>Weight Empty (lbs/kg):</b> 33070 lbs (15000kg)
<b>Capacity Imperial Gallons:</b> 13163	<b>Weight Full (lbs/kg):</b> 169204 lbs (76750kg)
<b>Capacity US Gallons:</b> 15809	<b>Tank Designed To Contain:</b> Diesel/Lubricants
<b>Dimension Length (mm/in):</b> 12192 mm/480"	<b>Environmental standard:</b> COP Regulations (PPG2)
<b>Dimension Width (mm/in):</b> 2438 mm/96"	<b>Approvals (Frame):</b> ISO 668:1995 CSC plated
<b>Dimension Height (mm/in):</b> 2896 mm/114"	<b>Design Standard:</b> COP Regulations (PPG2)
<b>Dimension Cabinet Opening (mm/in):</b> 2150 mm x 750 mm x 1150mm/ 84.65" x 29.53" x 45.28	BS799 part 5 Type J, Test pressure 6.3 psi (45KPA),
	<b>Approvals (Tank):</b> UL 142, ULC S601

