












**SPECIFICATION DATA SHEET | MODEL : TRANSTANK P31**



-  Self bunded or double wall design
-  Overfill protection supplied with mechanical shutoff and audible / visual alarm
-  Free to air vent with weather cap
-  Calibrated fluid level dipstick
-  Antisyphon valve installed
-  Ladder can be fitted to either side
-  Tank floor has fall to front for water collection
-  Bunded (spill contained) pump bay housing with removable ventilation panels
-  Front mounted security doors
-  Statutory signage
-  Under tank visibility

**SPECIFICATIONS**

STANDARD FITTINGS: 80 nb Camlock male tanker hose filler with dust cap connect, Tanker full point supplied with 80nb full bore, fire safe flanged ball valve and wafer style non return valve, container corner castings, statutory access manway, permanent ladder and platform, water evacuation pipe, interstitial space fluid dipstick, containment compartment with pressure vent, marine grade polyurethane paint (white in color)

|  |  |
|--|--|
| <b>Capacity (Brim-Fill) Litres:</b> 30280          | <b>Dimension Height (mm/in):</b> 2896 mm/114"        |
| <b>Capacity (Brim-Fill) Imperial Gallons:</b> 6660 | <b>Weight Bare Tank (lbs/kg):</b> 14991 lbs (6800kg) |
| <b>Capacity (Brim-Fill) US Gallons:</b> 7999       | <b>Approvals:</b> UL142, ULCS601, AS1940,            |
| <b>Dimension Length (mm/in):</b> 6058 mm/239"      | AS1692, AS1657                                       |
| <b>Dimension Width (mm/in):</b> 2438 mm/96"        |  |